


SPECIFICATIONS

1. RATING : 0.5mA 12VDC MAX .
2. CONTACT RESISTANCE : 100 mΩ MAX .
3. INSULATION RESISTANCE : 500 V DC , 100 MΩ MIN
4. OPERATING TEMPERATURE : -20℃ ~ 70℃ .
5. OPERATING FORCE : 160±50gf . 250±50gf
6. OPERATING LIFE : 100,000 CYCLES .

	<h1>广东科斯达开关厂</h1>					9				
	TITLE : LLUMINATED TACTILE SWITCH					8				
	MODEL :					7				
DRAWING NO. : -					6	CAP	ABS/PC	1	SLIVER /BLACK	
					5	CONTACT	PBS	1	Ag CLAD	
					4	TERMINAL	BRASS STRIP	4	Ag PLATED	
					3	BASE	PA66	1	BLACK	
					2	COVER	PET	1	NATURAL	
					1	KNOB	PA66	1	WHITE	
UNIT : M M	DWN.	LSX	2015-02-18	GENERAL TOLERANCE	NO.	PART NAME	MATERIAL	QTY.	FINISHING	
SCALE : 5 : 1	CHK'D	LJ	2015-02-18	WITHIN 1.5mm±0.1mm						
LEVEL 1	REV R1	APPD.	CC	2015-02-18						
				OVER 1.5mm±0.2mm						