



FEATURES

- Light operating force.
- Long term low contact resistance.
- Momentary or latching operation.
- Short stroke 2.0mm to latch.
- Compact spacing on PCB of 8.5mm.

SPECIFICATIONS

1.ELECTRICAL

● Contact rating	0.1A, 30VDC
● Contact resistance	50mWMax.
● Insulation resistance	100MWMIn. at 250VDC
● Dielectric strength	250VAC Min. for 60 sec.

2.MECHANICAL AND ENVIRONMENTAL

● Temperature rating	Operating: -15℃ to +55℃ Storage: -25℃ to +65℃
● Operation force	160±80gf
● Stroke	Lock Stroke: 2.0±0.2mm Full Stroke: 2.5±0.2mm
● Operating life	full load: 1x10 ⁴ cycles no load: 1x10 ⁵ cycles
● Contact form	DPDT

OPERATION	W:NO LOCK Z:LOCK
-----------	------------------

ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK
⑦	Contact	—	2	Phosphor bronze	Plating silvering	
⑥	Terminal	—	6	Brass	Plating silvering	
⑤	Spring	—	1	Sus	Natural	
④	Base	—	1	Pbt		
③	Crochet Needle	—	1	Sus	Natural	
②	Cover	—	1	Pom		
①	Keystake	—	1	Pom		

MARK	DESCRIPTION	DATE	REVISED	APPROVED	ANGLAR	±5°	DSND	DATE	SCALE: N/A	MODEL TYPE:		
ΔX					X.X	±0.2mm	DWN	DATE	VIEW:	KEY SWITCH		
ΔX					X.XX	±0.1mm	CHKD	DATE	UNIT: mm	PART NO.:		
ΔX					X.XXX	±0.05mm	APPD	DATE	SIZE: A4	DWG NO.:		
REVISIONS						UNSPECIFIED TOLERANCES	Kosod Technology Co., Ltd.			WEIGHT	SHEET	REVISION
www.bodongkaiguan.net						www.ksdkg.com				1.0g	1/1	A0