



受外力碰触或摇晃而瞬间导通

外管体：Brass ,nickel-plated  
 弹簧：Stainless steel  
 铜管：Brass ,silver-plated  
 封口胶：epoxy resin  
 焊接温度： $260^{\circ}\text{C} \pm 10^{\circ}\text{C}$   
 操作寿命：200,000 cycles  
 不可使用强酸，碱性助焊剂。

- ▶ 电压：1.5-12V
- ▶ 电流：<20mA
- ▶ 导通时间：about 2ms
- ▶ 闭路电阻：<30 ohm
- ▶ 开路电阻：>10M ohm
- ▶ 耐温:Operating:  $-40^{\circ}\text{C}$  to  $80^{\circ}\text{C}$
- ▶ 端子拉力:300gf for 1 minute
- ▶ 湿度:95% RH,  $40^{\circ}\text{C}$  for 96 hours

PART NAME		TILT SENSOR SWTICH		DRAWING	G.C.Chen	DWG.No.	SBIRB6
PART NO.				CHECK	G.C.Chen	REV.	A
UNIT: mm	TOLERANCE	UP TO 5	$\pm 0.2$	APPROVAL	DATE		
	OTHERWISE	ABOVE 5~30	$\pm 0.3$				
		ABOVE 30	$\pm 0.5$	SCALE	5:1	PAGE	1 OF 1
		ANGLE	$\pm 3'$				