


电路简图



开关技术特性(Switch technical Characteristics):

项目 (ITEM)	技术参数 (technical parameter)	特性值 (Value)
1	电气额定值 (Electrical Rating)	10(1.5)A/16(3)A/10(3)A 250VAC
2	接触电阻 (Contact Resistance)	≤50mΩ (初始值 Initial value)
3	绝缘电阻 (Insulation Resistance)	≥100MΩ (500VDC)
4	耐压强度 (Dielectric Voltage)	同极不相接端子间 (between non-connected terminals)
		端子与外壳或非载流金属零件之间 (between terminals and the metal frame)
5	电气寿命 (Electrical Life)	1500V/0.5mA/60S
6	机械寿命 (Mechanical Life)	≥10000 cycles
7	工作温度 (Operating Temperature)	≥10000 cycles
8	操作频率 (Operating Frequency)	≥100000 cycles
9	抗振动 (Vibration Proof)	0~125℃
10	可焊性 (Solder Ability): 超过 80% 的浸锡面积被焊料所覆盖 (More than 80% of immersed part shall be covered with solder)	电气 (electrical): 15 cycles
		机械 (Mechanical): 60 cycles
11	耐焊接热 (Solder Heat Resistance)	振动频率 (Vibration Frequency): 10~55HZ;
		振幅 (Amplitude): 1.5mm;
12	安全认证 (Safety Approvals)	三向 (Three directions): 1H
		焊接温度 (Soldering Temperature): 235±5℃
13	测试条件 (Test Conditions)	浸渍时间 (Immersing Time): 2~3S
		自动焊接 (Dip Soldering): 260±5℃ 5±1S
		手工焊接 (Manual Soldering): 300±5℃ 2~3S
		UL、CSA、VDE、ENEC、TUV、CE、CQC
		环境温度 (Ambient Temperature): 20±5℃
		相对湿度 (Relative Humidity): 65±5%RH
		大气压 (Air Pressure): 86~106KPa

NO.	PARTS	MATERIALS	Q'TY
8			
7			
6			
5	SPRING	SUS	1 NATURAL
4	CAM STICK	SUS	1 NATURAL
3	CASE	PA66/BRASS STRIP	1 GREY/Ag PLATED
2	COVER	PA66	1 BLACK
1	KNOB	PA66/PBS C5210R-EH	1 WHITE/Ag CLAD

TOLERANCE		UNLESS SPECIFIED	
WITHIN 1.5mm	: ±0.1mm	A	2012-8-13
OVER 1.5mm	: ±0.2mm	ISSUE	DATE
		初版	
		DESCRIPTIONS OF REVISION	
		APPD.	
TITLE : Micro Switch		UNIT : mm	DRWG NO.:
MODEL:		SCALE: 5:1	DWN.:
			2012-8-13
		CHK'D	
		APPD.	2012-8-13

