



SPEC:

A. Material:

1. Housing: PA66

2. Terminal:

Base: COPPER ALLOY

Base Plating: Ni 2.0 um

Surface Plating: Sn 3.0 um

B. Electrical Characteristics:

1. Rating: 15A 250V~ (UL, CUL)

10A 250V~ (VDE, CCC, SEMKO, NEMKO, DEMKO, FIMKO, KC)

2. Electric Strength: AC 2,000V FOR ONE MINUTE

3. Insulation Resistance: 100MΩ MIN. AT 500V DC

C. Approvals:

UL, CUL, VDE, CCC, SEMKO, NEMKO, DEMKO, FIMKO, KC

普通公差

COMMON TOLERANCE :

UP TO 5	±0.20
ABOVE 5 TO 30	±0.30
ABOVE 30	±0.50
ANGULAR	±5°

单位
UNIT
mm
绘图
DRAWN BY
日期
DATE

林晓良
19.08.12

投影
PROJECTED
核
CHECKED BY
核
APPROVAL BY

张平
周培雷

品名
PRODUCT NAME
型号
MODEL NO.
料号
PART NO.

AC power socket
KSD-AC JACK

REV. DATE REVISION DESCRIPTION ISSUE

广东科斯达电子科技有限公司
Guang dong Keside Electronic Technology Co., Ltd.