



1. FUNCTION: OFF-(ON)
2. RATING: UL/ENEC VDE/CQC: 16R(4)A 250V~ T125 5E4 μ
3. OPERATION FORCE: 140 \pm 50g.f
4. CONTACT RESISTANCE: \leq 50 m Ω
5. INSULATION RESISTANCE: \geq 100 M Ω
6. DIELECTRIC WITHSTAND: TERMINAL TO BUTTON 3000VAC/5mA/1MIN
TERMINAL TO TERMINAL 1500VAC/5mA/1MIN
7. CONTACT SPACING: < 3 mm

8. TRAVEL:

FREE POSITION	21.7 \pm 0.5mm
OPERATING POSITION	18.4 \pm 0.5mm
PRE TRAVEL	3.3 Max
OVER TRAVEL	1.0 Min

9. CIRCUIT DIAGRAM:



NO.	PARTS	MATERIALS	Q'TY	TOLERANCE UNLESS SPECIFIED	ISSUE	DATE	DESCRIPTIONS OF REVISION	APPD.	
8									
7									
6				WITHIN 1.5mm : \pm 0.1mm OVER 1.5mm : \pm 0.2mm	A	2012-8-13	初版		
5	SPRING	SUS	1	NATURAL					
4	CAM STICK	SUS	1	NATURAL					
3	CASE	PA66/BRASS STRIP	1	GREY/Ag PLATED					
2	COVER	PA66	1	BLACK					
1	KNOB	PA66/PBS C5210R-EH	1	WHITE/Ag CLAD					
				TITLE : Micro Switch			UNIT : mm	DRWG NO.:	
				MODEL:			SCALE: 5:1	DWN.	2012-8-13
							CHK'D		2012-8-13
							APPD.		