

DATE	DR.BY	ECN.NO.	DESCRIPTION	MARK	VER.
18/12'06			NEW DWG		AO

NOTE:

PRODUCT TO BE MET ROHS

1.MATERIAL

HOUSING: PA46+30%GF,UL94V-0,COLOR: BLACK

PLUNGER: BRASS,3u" GOLD PLATING

50u" MIN.NICKEL UNDERPLATEE.

BARREL:BRASS,3u" GOLD PLATING OVER

50u"MIN.NICKEL UNDER PLATED

SPRING:SUS304

2.SPECIFICATION

ELECTRICAL

CURRENT RATNG: 12VDC,1A

INSULATION RESISTANCE:100m Min

ENVIRONMENTAL

TEMPERATURE RANGE: -40°C ~85°C




3.MECHANICAL FUNCTION

SPRLNG PROBE FORCE

WORKING STROKE:100g±20gf AT 1.00mm RECOMMEND STROE

MAX.STROKE:1.30MM FULL STROKE

DURABILITY:10,000 CYCLES/1.00mm STROKE



1. 材料和电镀

接触头为(斜头)黄铜合金(C3604), 镀镍50-70 μ"镀金1 μ"

导管为黄铜合金(C3604), 镀镍50-70 μ"镀金1 μ"

2. 塑胶材质

PA46+30%玻纤

3. 弹力: 120g±10%

4. 持续工作电流: 1A

5. 工作电压: 12V AC/DC

接触电阻: 30mOhm Max

6. 使用寿命: 20000次


7. 工作温度计: -40°C - 80°C 90% R. H. Max

8. 中性盐雾测试24小时无锈蚀

-TOLERANCES-
UNLESS OTHERWISE SPECIFIED
公差参考表

X.	±0.10	X'	±2.00'
XX	±0.05		
XXX	±0.02	X.X'	±1.00'
X.XXX	——		

 **广东科斯达开关厂**



TITLE:
产品品名: POGO PIN

PRODUCT NO:
产品料号:

APPD: 核准:	王芬利	DATE	SCALE	UNIT	TYPE	PAGE
CHECK: 校对:		2016.11.21	1:1	mm	CD	1/1
DRAW: 绘图:						