



- 技术要求
1. 额定负荷: DC 5V 0.1~1mA
  2. 绝缘电阻:  $\geq 100M\Omega$
  3. 耐电压: AC100V 50Hz/1min
  4. 电器寿命: 50000次
  5. 环境温度:  $-10^{\circ} \sim +60^{\circ}$
  6. 相对湿度:  $40^{\circ}C \leq 95\%$
  7. 接触电阻:  $\leq 100M\Omega$
  8. 接触行程:  $0.5 \pm 0.2$
  9. 动作力:  $\leq 0.3N(31gf)$

TITLE	MICRO DETECTOR SWITCH			DRAWN		TOLERANCE OTHERWISE UNLESS SPECIFIED		9						
PART NO.				CHECKED		UP TO 5	±0.2	8						
DRAW NO.	M18			APPROVED		ABOVE 5 ~ 30	±0.3	7						
SCALE	4:1	UNIT	mm	DATE	06-12-2001	ABOVE 30 ~ 50	±0.4	6						
						ABOVE 50	±0.5	5						
						ANGLE	±3'	4	TERMINAL	BRASS	4	Ag PLATED OVER Ni PLATED		
<b>广东科斯达电子科技有限公司</b> Guangdong Keside Electronic Technology Co., Ltd.										2	COVER	NYLON	1	BLACK\Ag PLATED OVER Ni PLATED
										1	KNOB	NYLON	1	BLACK
										NO.	PARTS	MATERIAL	QTY.	FINISHING