



常態 FREE 1-2,4-5  
按下 PUSH 2-3,5-6  
SCHEMATIC (NON-SHORTING)

### SPECIFICATIONS

- (1)LIFE TEST:10000cycles at a speed of 15-18cycles
- (2)CONTACT RESISTANCE:100mΩmax
- (3)INSULATION RESISTANCE:100MΩmin
- (4)DIELECTRIC STRENGTH:250V AC FOR 1MIN
- (5)OPERATING TEMPERATURE:-16°C-+60°C
- (6)RATING: 0.1A 30V DC
- (7)FUNCTION:2P2T
- (8)TIMING:NON-SHORTING
- (9)OPERATING FORCE:180gf±50gf

NO.	PARTS	MATERIALS	Q'TY	TOLERANCE UNLESS SPECIFIED	ISSUE	DATE	DESCRIPTIONS OF REVISION	APPD.
8								
7								
6				WITHIN 1.5mm : ±0.1mm	A	2016-10-14	初版	
5	SPRING	SUS304	1	OVER 1.5mm : ±0.2mm	ISSUE	DATE	DESCRIPTIONS OF REVISION	APPD.
4	CAM STICK	SUS304	1		TITLE : VERTICAL PUSH SWITCH		UNIT : mm	DRWG NO.:
3	CASE	PA66/BRASS STRIP	1		MODEL:		SCALE: 5:1	DWN.
2	COVER	PA66+15%F.G	1					2016-10-14
1	KNOB	PA66+15%F.G/PBS STRIP	1				CHK'D	2016-10-14
							APPD.	