

P.C.B LAYOUT
BOTTOM VIEW




SCHEMATIC

SCHEMATIC (NON-SHORTING)

SPECIFICATIONS

- (1) LIFE TEST: 10000 cycles at a speed of 15-18 cycles
- (2) CONTACT RESISTANCE: 100mΩmax
- (3) INSULATION RESISTANCE: 100MΩmin
- (4) DIELECTRIC STRENGTH: 250V AC FOR 1MIN
- (5) OPERATING TEMPERATURE: -16°C - +60°C
- (6) RATING: 0.1A 30V DC
- (7) FUNCTION: 2P2T
- (8) TIMING: NON-SHORTING
- (9) OPERATING FORCE: 180gf ± 50gf

| | | | | | | | | | | |
|-----|-----------|-----------------------|------|----------------|---|-------|------------|--------------------------|-----------|------------|
| 8 | | | | | | | | | | |
| 7 | | | | | | | | | | |
| 6 | | | | | | | | | | |
| 5 | SPRING | SUS304 | 1 | NATURAL | | | | | | |
| 4 | CAM STICK | SUS304 | 1 | NATURAL | | | | | | |
| 3 | CASE | PA66/BRASS STRIP | 1 | GREY/Ag PLATED | | | | | | |
| 2 | COVER | PA66+15%F.G | 1 | BLACK | | | | | | |
| 1 | KNOB | PA66+15%F.G/PBS STRIP | 1 | BLACK/Ag CLAD | | | | | | |
| NO. | PARTS | MATERIALS | Q'TY | | | | | | | |
| | | | | | TOLERANCE UNLESS SPECIFIED | | | | | |
| | | | | | WITHIN 1.5mm : ±0.1mm | A | 2016-10-14 | 初版 | | |
| | | | | | OVER 1.5mm : ±0.2mm | ISSUE | DATE | DESCRIPTIONS OF REVISION | | APPD. |
| | | | | | TITLE : VERTICAL PUSH SWITCH | | | UNIT : mm | DRWG NO.: | |
| | | | | | MODEL: | | | SCALE: 5:1 | DWN. | 2016-10-14 |
| | | | | |  | | | | CHK'D | 2016-10-14 |
| | | | | | | | | | APPD. | |