



P.C.B LAYOUT TOP VIEW

**SPECIFICATION**

规格

Rating: DC 20V 5.5A

额定值: 直流20V 5.5A

Contact resistance: ≤0.03Ω

接触电阻: ≤0.03Ω

Insulation resistance: ≥100MΩ

绝缘电阻: ≥100MΩ

Withstand voltage :AC500V(50Hz)/min

耐受电压: AC500V (50Hz) /min

Insertion and extraction: 3-20N

插入和提取: 3-20N

Use temperature range: -30-70 °C

使用温度范围: -30-70 °C

Life test :5000 cycles

寿命试验: 5000次循环

SCHEMATIC	
Model	DC-C300-5.5A
Center Pin	Ø1.65 mm
	Ø2.0 mm
	Ø2.5 mm

	MATERIAL	PLATING
center pin	Brass	tin
coat	Brass	
cover palte	Sus	
terminal 1	Phosphor Bronze	tin
terminal 2	Phosphor Bronze	tin
terminal 3	Phosphor Bronze	tin
plastic	Ppa	

				ANGLAR	±5°	 SWITCH CONNECTOR	DSND		SCALE: N/A	MODEL TYPE: DC POWER JACK		
				L ≤ 4	±0.2		DWN		VIEW:	PART NO.: DC-C300-5.5A-2.5		
				4 < L ≤ 16	±0.3		CHKD		UNIT: mm/in	DWG NO.:		
				16 < L ≤ 63	±0.4		APPD		SIZE: A4			
				L > 63	±0.5							
REVISIONS						UNSPECIFIED TOLERANCES	KE SI DA ELECTRONIC TECHNOLOGY CO., LTD			WEIGHT	SHEET	REVISION
WWW.BODONGKAIGUAN.NET						WWW.CKJACK.COM	WWW.KSDKG.COM				1/1	A0