



Technolo Request:

1.Outlook:

N0 burr,no hurt.

2.Electronic performance:

a:Insulation resistance:

Above DC500V/100MΩ ;

b:Endure voltage:

AC500V at 1 minute;

c>Contact resistance:

Under 30MΩ ;

3.Insertion fore & withdrawal force;0.3-3kg

4.Salt spray test :24H.

	MATERIAL	PLATING
plastic	PBT	Black
terminal	C3604	NI
Spring	phosphor bronze	NI
Waterproof tube	C3604	NI
silicone pad		

REVISIONS				ANGULAR	±5°	DSND	SCALE: N/A	MODEL TYPE:		
				L ≤ 4	±0.2	DWN	VIEW:	DC POWER JACK		
				4 < L ≤ 16	±0.3	CHKD	UNIT: mm/in	PART NO.: DC-F2180		
				16 < L ≤ 63	±0.4	APPD	SIZE: A4	DWG NO.:		
				L > 63	±0.5					
				UNSPECIFIED TOLERANCES		SWITCH CONNECTOR		WEIGHT	SHEET	REVISION
WWW.BODONGKAIGUAN.NET				WWW.CKJACK.COM		KE SI DA ELECTRONIC TECHNOLOGY CO., LTD			1/1	A0