


SCHMATIC



SPECIFICATION

规格

1. Rating: DC 30V, 2A

额定值: 直流30V, 2A

2. Contact resistance: ≤0.02Ω

接触电阻: ≤0.02Ω

3. Insulation resistance: 100mΩ

绝缘电阻: 100mΩ

4. Withstand voltage: 250V/min

耐压: 250V/min

5. Insertion and extraction force: 3-15N

插拔力: 3-15N

6. life: 5,000 cycles

寿命: 5,000次循环

5	Terminal	1	Brass	Plating silvering
4	Terminal	1	Brass	Plating silvering
3	Terminal	1	Phosphor copper	Plating silvering
2	Cover	1	PBT	-
1	Plastic	1	PBT	-
LTR	PART NAME	1	MATERIAL	PLATED

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
ANGULAR				±5°
L ≤ 4				±0.2
4 < L ≤ 16				±0.3
16 < L ≤ 63				±0.4
L > 63				±0.5
WWW.BODONGKAIGUAN.NET WWW.CKJACK.COM WWW.KSDKG.COM				

DSND	SCALE: N/A	MODEL TYPE: DC POWER JACK
DWN	VIEW:	PART NO.: DC-011-2.0A-0.65
CHKD	UNIT: mm/in	DWG NO.:
APPD	SIZE: A4	
KE SI DA ELECTRONIC TECHNOLOGY CO., LTD		
WEIGHT	SHEET	REVISION
	1/1	A0