



SPECIFICATION

1. Rating : DC 20V 5.5A;
2. Contact resistance : < 0.03Ω;
3. Insulation resistance : 2100MΩ (DC250V);
4. Withstand voltage : 500VAC
5. Insertion and extraction

SCHMATIC	
Model	DC-C033D-5.5A
Center Pin	Ø2.0 mm
	Ø2.5 mm

	MATERIAL	PLATING
center pin	Brass	tin
coat	Sus	
terminal 2	Phosphor Bronze	tin
terminal 3	Brass	tin
terminal 4	Brass	tin
terminal 5	Brass	tin
plastic	Pa9t	

				ANGLAR	±5°	 SWITCH CONNECTOR	DSND		SCALE : N/A	MODEL TYPE: DC POWER JACK			
				L ≤ 4	±0.2		DWN		VIEW:	PART NO.: DC-C033D-5.5A-2.0			
				4 < L ≤ 16	±0.3		CHKD		UNIT: mm/in	DWG NO.:			
				16 < L ≤ 63	±0.4		APPD		SIZE: A4				
				L > 63	±0.5								
REVISIONS				DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES						
WWW.BODONGKAIGUAN.NET				WWW.CKJACK.COM		WWW.KSDKG.COM		KE SI DA ELECTRONIC TECHNOLOGY CO., LTD			WEIGHT	SHEET	REVISION
												1/1	A0