



Temperature : -20~70 C
 温度: -20~70 C
 Rated Load: DC 30V 0.3A
 额定负载: DC 30V 0.3A
 Contact Resistance : <0.03
 接触电阻 : <0.03
 Insulation Resistance: >100M
 绝缘电阻: >100M
 Withstand Voltage : AC500V(50Hz)/min
 耐受电压 : AC500V(50Hz)/分钟
 Actuating Force : 8~30N
 驱动力: 8~30N
 Life : 3000N
 寿命: 3000N

	MATERIAL	PLATING
termina 1	Phosphor Bronze	ag
termina 2	Phosphor Bronze	ag
termina 3	Phosphor Bronze	ag
termina 4	Phosphor Bronze	ag
terminal 5	Phosphor Bronze	ag
copper bush	Brass	tin
base	PA66	
cover	PA66	
Shell	SUS	

REVISIONS				ANGULAR	±5°	DSND	SCALE: N/A	MODEL TYPE:		
				L ≤ 4	±0.2	DWN	VIEW:	ERAPHONE SOCKET		
				4 < L ≤ 16	±0.3	CHKD	UNIT: mm/in	PART NO.: PJ-379-X		
				16 < L ≤ 63	±0.4	APPD	SIZE: A4	DWG NO.:		
				L > 63	±0.5					
				UNSPECIFIED TOLERANCES						
KE SI DA ELECTRONIC TECHNOLOGY CO., LTD								WEIGHT	SHEET	REVISION
WWW.BODONGKAIGUAN.NET WWW.CKJACK.COM WWW.KSDKG.COM									1/1	A0

KSD
SWITCH CONNECTOR