




Temperature :-20~70C
 Rated Load: DC 30V 0.3A
 Contact Resistance :<0.03
 Insulation Resistance: >100M
 Withstand Voltage :AC500V(50Hz)/min
 Actuating Force :2.2~30N
 Life :3000N

PIN	PJ-305-X
Schematic	<p>G:Green R:Red</p>



	MATERIAL	PLATING
terminal 1	Brasse	ag
terminal 2	Phosphor Bronze	ag
terminal 3	Phosphor Bronze	ag
terminal 4	Phosphor Bronze	ag
terminal 5	Phosphor Bronze	ag
plastic	Pbt	

REVISIONS				DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	DSND	SCALE: N/A	MODEL TYPE: ERAPHONE SOCKET		
			ANGLAR				±5°	DWN	VIEW:	PART NO.: PJ-305-X		
			L ≤ 4				±0.2	CHKD	UNIT: mm/in	DWG NO.:		
			4 < L ≤ 16				±0.3	APPD	SIZE: A4			
			16 < L ≤ 63				±0.4					
			L > 63				±0.5					
WWW.BODONGKAIGUAN.NET WWW.CKJACK.COM WWW.KSDKG.COM								KE SI DA ELECTRONIC TECHNOLOGY CO., LTD		WEIGHT	SHEET	REVISION
										1/1	A0	

KSD
SWITCH CONNECTOR