



Contact Rating: AC/DC 42V, 100mA
 触点额定值: AC/DC 42V, 100mA
 Mechanical Life: 1,000,000 cycles
 机械寿命: 1000000cycles
 Contact Resistance: 100 mΩ max. initial
 接触电阻: 100 mΩ max. initial
 Insulation Resistance: 1,000 MΩ min. 100VDC
 绝缘电阻: 1,000 MΩ min. 100VDC
 Dielectric Strength: 250VDC/1 min.
 介电强度: 250VDC/1 min.
 Operating Temperature: -40°C to 80°C
 工作温度: -40°C to 80°C

				ANGLAR	±5°	KSD SWITCH CONNECTOR	DSND		SCALE: N/A	MODEL TYPE: TACT SWITCH		
				L ≤ 4	±0.2		DWN		VIEW:	PART NO.: TS-1206		
				4 < L ≤ 16	±0.3		CHKD		UNIT: mm/in	DWG NO.:		
				16 < L ≤ 63	±0.4		APPD		SIZE: A4			
				L > 63	±0.5							
DATE	REVISED	APPROVED		UNSPECIFIED TOLERANCES			KE SI DA ELECTRONIC TECHNOLOGY CO., LTD			WEIGHT	SHEET	REVISIC
WWW.BODONGKAIGUAN.NET WWW.CKJACK.COM WWW.KSDKG.COM											1/1	A0