


Circuit diagram



Technical Parameters

1. Electrical Rating: 0.1A 125/250VAC
3A/12VDC; 0.1A/48VDC
2. Electrical lifetime: 100 000
3. Mechanical lifetime: 100 000
4. Contact Resistance: ≤100mΩ
5. Operating force: 2.5N MAX
6. Pretravel: 0.3~1.0mm
7. Withstand Voltage: Feet and Feet 500V/5S/5mA
Feet and Shell 1500V/5S/5mA
8. Insulation Resistance: ≥100MΩ (Test Voltage 500VDC)
9. Proof Tracking Index (PTI): 175V
10. Ambient temperature: 85°

Waterproof grade: IP67

1	Rubber shell	PA66
2	seal ring	Silica gel
3	base	Brass+PA66
4	According to sincerity	POM
5	Contact moving plate	C5191+AgNi10
6	Strut	SUS301-H

				ANGULAR	±5°	 SWITCH CONNECTOR	DSND		SCALE: N/A	MODEL TYPE:	Microswitch	
				L ≤ 4	±0.2		DWN		VIEW:	PART NO.:	DF1-136UWY-3	
				4 < L ≤ 16	±0.3		CHKD		UNIT: mm/in	DWG NO.:		
				16 < L ≤ 63	±0.4		APPD		SIZE: A4			
				L > 63	±0.5							
REVISIONS						UNSPECIFIED TOLERANCES	KE SI DA ELECTRONIC TECHNOLOGY CO., LTD			WEIGHT	SHEET	REVISION
WWW.BODONGKAIGUAN.NET						WWW.CKJACK.COM	WWW.KSDKG.COM				1/1	A0