


Technical Parameters



1. Electrical Rating: 0.1A 125/250VAC  
3A/12VDC; 0.1A/48VDC
2. Electrical lifetime: 100 000
3. Mechanical lifetime: 100 000
4. Contact Resistance: ≤100mΩ
5. Operating force: 1.3N MAX
6. Operation Position: 6.75±0.2mm
7. Pretravel: 0.8mm(MAX)
8. Withstand Voltage: Feet and Feet 500V/5S/5mA  
Feet and Shell 1500/5S/5mA
9. Insulation Resistance: ≥100MΩ (Test Voltage 500VDC)
10. Proof Tracking Index (PTI): 175V
11. Ambient temperature: 125°

1	Rubber shell	PA66
2	seal ring	Silica gel
3	base	Brass+PA66
4	According to sincerity	POM
5	Contact moving plate	C5191+AgNi10
6	Strut	SUS301-H

Circuit diagram



Waterproof grade: IP67

				ANGLAR	±5°	 SWITCH CONNECTOR	DSND		SCALE: N/A	MODEL TYPE:	Microswitch		
				L ≤ 4	±0.2		DWN		VIEW: 	PART NO.:	DF1-000NS-1		
				4 < L ≤ 16	±0.3		CHKD		UNIT: mm/in	DWG NO.:			
				16 < L ≤ 63	±0.4		APPD		SIZE: A4				
				L > 63	±0.5					WEIGHT	SHEET	REVISION	
REVISIONS				DATE	REVISED	APPROVED	KE SI DA ELECTRONIC TECHNOLOGY CO., LTD				1/1	A0	
UNSPECIFIED TOLERANCES				WWW.BODONGKAIGUAN.NET				WWW.CKJACK.COM				WWW.KSDKG.COM	