



SPECIFICATION

产品规格

1. Rating: DC 30V 0.5A

额定值: DC 30V 0.5A

2. Contact resistance: <0.03Ω;

接触电阻: <0.03Ω;

3. Insulation resistance: >100MΩ(DC250V)

绝缘电阻: >100MΩ(DC250V)

4. Withstand voltage: 500VAC;

耐受电压: 500VAC;

5. Insertion and extraction force: 3-30N;

插拔力: 3-30N;

6. life test: 5,000 cycles.

寿命试验: 5000次循环.

料号	Color
PJ-3043-B	BLACK
PJ-3043-R	Red
PJ-3043-G	Green

	MATERIAL	PLATING
8 SHELL	1 SUS301 0.2t	Ni60U"
7 HOUSING	1 PA9T	
6 CONTACT FOOT	1 COPPER ALLOY C5191	Ag15u" OVER Ni20U"
5 SPRING PIECE	1 COPPER ALLOY C5191	Ag15u" OVER Ni20U"
4 CURVE PIECE	1 COPPER ALLOY C5191	Ag15u" OVER Ni20U"
3 SPRING PIECE	1 COPPER ALLOY C5191	Ag15u" OVER Ni20U"
2 SPRING PIECE	1 COPPER ALLOY C5191	Ag15u" OVER Ni20U"
1 CONTACT FOOT	1 COPPER ALLOY C5191	Ag15u" OVER Ni50U"

REVISIONS				DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	DSND	SCALE: N/A	MODEL TYPE: 3.5 PHONE JACK	WEIGHT	SHEET	REVISION
							ANGULAR ±5°						
							L ≤ 4 ±0.2						
							4 < L ≤ 16 ±0.3						
							16 < L ≤ 63 ±0.4						
							L > 63 ±0.5						
								CHKD	UNIT: mm/in	PART NO.: PJ-3043-X			
								APPD	SIZE: A4	DWG NO.:			
								KE SI DA ELECTRONIC TECHNOLOGY CO., LTD					
WWW.BODONGKAIGUAN.NET WWW.CKJACK.COM WWW.KSDKG.COM												1/1	A0

