



U221-04XN-1BU07-X1

- 1:SPCC
- S:Scrolls F:Flat
- W:WHITE B:BLACK
- 1:PB
- 2:PA6T
- 3:PA9T
- 4:LCP
- 1:Au 1U"
- 5:Au 15U"
- 6:Au 30U"

Housing Material: PBT UL94V-0, black/White
 Contact Terminal: C2680
 Metallic Shell: Spcc430
 CONTACT: UNDER PLATED 50u" MIN. NICKEL ALL
 OVER 100u" MIN. TIN IN SOLDERING
 AREA GOLD PLATED IN CONTACT AREA.
 Salt Spray Test Requirements: Test 12H
 High temperature resistance of gelatinous heart:200°~220°
 Contact Resisance.
 30 milliohms MAX
 Dielectric Withstanding Voitage:
 500 V AC AT Sea Levol
 Insulation Resistance:
 1000MEGA ohms MIN



				ANGLAR	±5°	DSND		SCALE: N/A	MODEL TYPE: USB 2.0			
				L ≤ 4	±0.2	DWN		VIEW:	PART NO.:			
				4 < L ≤ 16	±0.3	CHKD		UNIT: mm/in	DWG NO.:			
				16 < L ≤ 63	±0.4	APPD		SIZE: A4	U221-04XN-1BU07-F1			
				L > 63	±0.5				WEIGHT	SHEET	REVISION	
DESCRIPTION				DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES					
REVISIONS							KE SI DA ELECTRONIC TECHNOLOGY CO., LTD			1/1	A0	
WWW.BODONGKAIGUAN.NET				WWW.CKJACK.COM			WWW.KSDKG.COM					

