



SHAFT SHOWN IN FULL  
C. C. W POSITION



P. C. B MOUNTING HOLE DETAIL



**KSD** RV166 SERIES ROTARY POTENTIOMETERS  
SWITCH CONNECTOR RV166 旋转电位器

Electrical characteristics 电气特性

Total Resistance Range 总阻值	1K≤TR≤1MΩ
Resistance Tolerance 总阻值容许公差	±20%
Resistance Taper 阻值线性	A,B,C taper.
Rating Power 额定功率	B taper: 0.2W ; Other taper: 0.1W
Slide Noise 杂讯	Less than 100mV
Residual Resistance Value 残留阻值	Less than 20Ω
Dielectric Voltage 耐电压	For 1 minute or more AC 500V
Insulation resistance 绝缘阻抗	More than 100MΩ at DC 500V
Tracking Error 同步误差	-40~0 dB ≤ ±3dB
Switch Contact Resistance 开关接触电阻	Less than 200mΩ


Mechanical characteristics 机械特性

Total Rotational Angle 旋转角度	300°±10°
Rotational Torque 旋转力矩	20gf.cm~200 gf.cm
Number of click 档位数量	1CC,11CC,21CC,41CC
Click Torque 档位力矩	100gf.cm~300 gf.cm
Stop Strength 止挡强度	6kgf.cm
Shaft Push & Pull Strength 轴推拉强度	8kgf.cm
Switch Rotation Angle 开关旋转角度	50°±10°
Switch Action 开关作动力	100~450gf.cm

Environmental characteristics

Rotational Life 旋转寿命	10,000 cycles
----------------------	---------------

RV166 轴心规格



\* 具体轴心规格, 可依据客户需求订做。  
Specific axis specifications can be customized according to customer needs.

**广东科斯达电子科技有限公司**  
KSDKG Guang dong Keside Electronic Technology Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED:  
 Up to 5 ±0.2  
 Above 5 ~ 15 ±0.3  
 Above 15 ~ 30 ±0.4  
 Above 30 ~ 50 ±0.5  
 Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	ROTARY POTENTIOMETER
Jack Lu	07/23/13	FINISH	MODLE	旋转电位器系列
CHECKED BY:	DATE	SCALE	DWG NO.	KSD-RV-1667NS
Jacky Chen	07/23/13	SHEET NO.	PART NO.	
APPROVED BY:	DATE			SIZE
Tony Kao	07/23/13			A4
				VER
				R2