



P. C. B MOUNTING HOLE DETAIL

Electrical characteristics 电气特性	
Rating Power 额定功率	DC30V 0.3A
Contact Resistance 接触阻抗	Less than 50mΩ
Dielectric Voltage 耐电压	For 1 minute or more AC 500V
Insulation Resistance 绝缘阻抗	More than 100MΩ at DC 500V
Mechanical characteristics 机械特性	
Changeover Angle 切换角度	30°±3°
Rotational Torque 旋转力矩	1.3kgf.cm ±0.3kgf.cm
Number Of Positios 接点数	2 to 12
Number Of Poles 极数	1 & 2
Shaft Stop Strength 止动强度	3kgf.cm
Environmental characteristics	
Rotational Life 旋转寿命	10,000 cycles

广东科斯达电子科技有限公司
KSDKG Guang dong Keside Electronic Technology Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S



UNITS MM

DRAWN BY: Jack Lu DATE: 07/23/13
 CHECKED BY: Jacky Chen DATE: 07/23/13
 APPROVED BY: Tony Kao DATE: 07/23/13

MAT'L		TITLE	KSD-RS ROTARY SWITCH
FINISH		MODLE	KSD-RS旋转开关系列
SCALE	1 : 1	DWG NO.	KSD-RS-26
SHEET NO.	1 of 1	PART NO.	
		SIZE	A4
		VER	R2

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	公差及料號更新	Jack	072313
1	圖面更新	Frank Wu	021012