



P. C. B MOUNTING HOLE DETAIL

Electrical characteristics 电气特性

Rating Power 额定功率	DC16V 0.5A
Contact Resistance 接触阻抗	Less than 50mΩ
Dielectric Voltage 耐电压	For 1 minute or more AC 500V
Insulation Resistance 绝缘阻抗	More than 100MΩ at DC 500V

Mechanical characteristics 机械特性

Changeover Angle 切换角度	30°±3°
Rotational Torque 旋转力矩	300gf.cm~700 gf.cm
Number Of Positios 接点数	1口 2口 3口 4口 5口 6口 7口 8口
Number Of Poles 极数	2口 3口 4口 5口 6口

Environmental characteristics

Rotational Life 旋转寿命	10,000 cycles
----------------------	---------------

L	15	20	25	W		5	7	H		10	12.5
F	6	10	10								

广东科斯达电子科技有限公司
KSDKG Guang dong Keside Electronic Technology Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S



UNITS MM

DRAWN BY: Jack Lu DATE: 07/23/13
CHECKED BY: Jacky Chen DATE: 07/23/13
APPROVED BY: Tony Kao DATE: 07/23/13

MAT'L		TITLE	KSD-RS ROTARY SWITCH
FINISH		MODLE	KSD-RS旋转开关系列
SCALE	1 : 1	DWG NO.	KSD-RS-1201
SHEET NO.	1 of 1	PART NO.	

2	公差及料號更新	Jack	072313
1	圖面更新	Frank Wu	021012
ITEM NO.	DESCRIPTION	DRAWN	DATE

SIZE A4
VER R2