



Electrical characteristics 电气特性	
Rating Power 额定功率	DC5V 10mA
Fluttering 振荡	T1,T3≤3ms
Sliding Noise(Bounce)滑动杂音	T2≤2ms
Dielectric Voltage 耐电压	For 1 minute or more AC 300V
Insulation resistance 绝缘阻抗	More than 100MQ at DC 250V
Phase Difference 相位差	ΔT±0.08T
Mechanical characteristics 机械特性	
Total Rotational Angle 旋转角度	360°
Rotational Torque 旋转力矩	30gf.cm~200 gf.cm
Number of click 档位数量	30 Detents(Angle:12°±2°) 20 Detents(Angle:18°±2°)
Push-Pull Strength 轴推拉强度	10Kgf.cm Min for 10Sec
Bushing & nut tight strength 轴套锁紧强度	10.0Kgf Min
Switch Specifications 开关特性	
Maximum Ratings 额定电压	DC5V 10mA(1mA Min)
Contact resistance 接触阻抗	200mΩ Max
Travel of switch 开关移动量	0.5+0.4/-0.3 mm OR 1.5+0.4/-0.3 mm
Operating force of switch 开关动作力	500±200gf
Environmental characteristics	
Rotational Life 旋转寿命	30,000 cycles
Switch Life 开关寿命	20,000 cycles

EC11 轴心轴套规格

F-TYPE	D=3.5	D=5	D=7	D=10	Y-TYPE	D=3.5	D=5	D=7	D=10
	L 9 10 F 4 4	L 10 12.5 13 15.5 16.7 F 4 6 7 5 7	L 12.5 13 15 17 20 F 4 4 5 7 7	L 29.5 32 F 9 12		L 8.5 F 3.5	L 9.5 11 11.5 12.5 F 4 4.5 5 5	L 12.5 13.5 15.5 F 4 5 5	L 19.5 F 6

输出信号

轴的旋转方向 Shaft Rotational direction	信号 Signal	正向 Direction	反向 Reverse
顺时针方向 C.W.	A(A~C端子间) A(Terminal A~C)		
逆时针方向 C.C.W.	B(B~C端子间) B(Terminal B~C)		

*具体轴心规格, 可依客户需求订做。
Specific axis specifications can be customized according to customer needs.

广东科斯达电子科技有限公司
KSDKG Guang dong Keside Electronic Technology Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED:
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L	TITLE	EC ENCODING SWITCH
Jack Lu	07/23/13			
CHECKED BY:	DATE	FINISH	MODLE	EC编码开关系列
Jacky Chen	07/23/13			
APPROVED BY:	DATE	SCALE	DWG NO.	KSD-EC-1102S
Tony Kao	07/23/13	1 : 1		
		SHEET NO.	PART NO.	SIZE
		1 of 1		A4
				VER
				R2