


REMARK:


SIDE A :  **KSD**  
 16A(RES) 125VAC  
 U16WR 12A(IND) 125VAC  
 3 2 1




SIDE B : 6(4)A 5E4  
 10(6)A  
 250V~T85/55

KNOB COLOUR IS RED  
 TAB TERMINAL NOT FOR SOLDERING

Panel Cut-out Dimensions



Panel Thickness (mm/inch)	DIM X <sup>+0.1</sup> <sub>-0.1</sub> (mm/inch)	DIM Y <sup>+0.1</sup> (mm/inch)
0.5~1.2 (.02~.05)	19.4 (.764)	13.1 (.516)
1.2~2.0 (.05~.08)	19.7 (.775)	
2.0~3.0 (.08~.12)	20.0 (.787)	

ISSUED	SPECIFICATION (INITIAL)	TITLE: ROCKER SWITCH 1P1T			
	RATING: AC 125V 16A	MODEL NO: U16WR-11N01-R1(RB)R-00			
	CONTACT RESISTANCE: MAX. 30mΩ	UNIT: mm	DWN	YANG	20/05/06
	INSULATION RESISTANCE: 500MΩ at 500V DC	SCALE: 2 : 1	CHK'D		
	WITHSTAND VOLTAGE: AC 1000V for 1 min	TOLERANCE: ±0.2	APPD.		
	OPERATION FORCE: 600±250g				
	SWITCHING LIFE: 10000 Cycles(6-10c/m loading)				
BY:	 <b>广东科斯达电子科技有限公司</b> GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.	DRWG NO:			
DATE:		A60288-00			