



**Order Code 选型表**

Type	Poles	Circuit	Push Length	Terminals
ex) SP	1	2	S	H

1 Single  
 1 OFF-(ON)  
 2 Momentary  
 F 0 mm  
 S 5.4 mm  
 P Straight  
 B Straight W / Bracket  
 H Right Angle W / Bracket  
 V Vertical W / Bracket

**General Specification 产品性能**

- Rating 工作电压/电压: 0.4VA at 28V AC or DC Max.
- Contact Resistance 接触电阻: Max 50mΩ
- Insulation Resistance 绝缘电阻: Min 500MΩ, at DC 500V
- Operating Force 操作力: 1 Minute at AC 500V
- Life Cycle 使用寿命: 250±100gf (1 pole), 350±100gf (2pole)
- Travel 移动: 1.1mm
- Ambient Temp. Range 环境温度范围: -30°C ~ +85°C
- Solder Conditions 焊接方式: 5 sec, 270°C

MODEL	POLES	CIRCUIT		SCHEMATICS
		NORMAL	DOWN	
SP-11	SPST	OFF	(ON)	
SP-12	SPDT	ON 2-3	(ON) 1-2	

**广东科斯达电子科技有限公司**  
**GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.**

TOLERANCE UNLESS OTHERWISE STATED:  
 Up to 5 ±0.2  
 Above 5 ~ 15 ±0.3  
 Above 15 ~ 30 ±0.4  
 Above 30 ~ 50 ±0.5  
 Angle ±0.3

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	12/27/22	FINISH	MODLE	SWITCH
CHECKED BY:	DATE	SCALE	DWG NO.	SP-12SV
Jacky Chen	12/27/22	SHEET NO.	PART NO.	
APPROVED BY:	DATE			
Tony Kao	12/27/22			

ITEM NO.	DESCRIPTION	DRAWN	DATE