



Order Code 选型表

Type	Poles	Circuit	Push Length	Terminals
ex) SP	1	2	S	H

1 Single
 1 OFF-(ON)
 F 0 mm
 S 5.4 mm
 P Straight
 B Straight W / Bracket
 H Right Angle W / Bracket
 V Vertical W / Bracket

General Specification 产品性能

- Rating 工作电压/电压: 0.4VA at 28V AC or DC Max.
- Contact Resistance 接触电阻: Max 50mΩ
- Insulation Resistance 绝缘电阻: Min 500MΩ, at DC 500V
- Operating Force 操作力: 1 Minute at AC 500V
- Life Cycle 使用寿命: 250±100gf (1 pole), 350±100gf (2pole)
- Travel 移动: 1.1mm
- Ambient Temp. Range 环境温度范围: -30°C ~ +85°C
- Solder Conditions 焊接方式: 5 sec, 270°C

MODEL	POLES	CIRCUIT		SCHEMATICS
		NORMAL	DOWN	
SP-11	SPST	OFF	(ON)	
SP-12	SPDT	ON 2-3	(ON) 1-2	

广东科斯达电子科技有限公司
GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGLE'S

DRAWN BY: Jack Lu 12/27/22
 CHECKED BY: Jacky Chen 12/27/22
 APPROVED BY: Tony Kao 12/27/22

MATL
 FINISH
 SCALE 1 : 1
 SHEET NO. 1 of 1

TITLE SWITCH
 MODLE SWITCH
 DWG NO. **SP-12FH**
 PART NO.

SIZE A4
 VER R

ITEM NO.	DESCRIPTION	DRAWN	DATE