









# TS4-6



<b>Specifications</b>	
Circuit	:SPST
Current rating	:30mA
Voltage rating	:30VDC
Dielectric withstanding voltage	:250VAC for 1 minute
Contact resistance	:30mΩ Max. (Initial)
Insulation resistance	:100MΩ Min
Operating force	:250±50gf
Total travel	:1.0mm±0.2mm
Operating life	:100,000 cycles Min.
Solder specifications	:260±5° C for 5 seconds
Operating temperature	:-20° C ~ +60° C
Welding method	:Manual Soldering (350° C±5° C, 3s±0.5s)



P.C.B.LAYOUT



CIRCUIT

Y	Yellow	黄色
W	White	白色
U	Blue	蓝色
R	Red	红色
O	Orange	橙色
G	Green	绿色
B	Black	黑色
A	Gray	灰色
CAP COLOR (X)		

 **广东科斯达电子科技有限公司**  
GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.

TOLERANCE UNLESS OTHERWISE STATED:  
 Up to 5 ±0.2  
 Above 5 ~ 15 ±0.3  
 Above 15 ~ 30 ±0.4  
 Above 30 ~ 50 ±0.5  
 Angle ±0.3



UNITS MM

DRAWN BY:	DATE
Jack Lu	12/27/22
CHECKED BY:	DATE
Jacky Chen	12/27/22
APPROVED BY:	DATE
Tony Kao	12/27/22

MATL	TITLE	SWITCH
FINISH	MODLE	TACT SWITCH WITH LED
SCALE 1 : 1	DWG NO.	SIZE A4
SHEET NO. 1 of 1	PART NO.	VER R

ITEM NO.	DESCRIPTION	DRAWN	DATE