


ELECTRICAL RATING:
 Resistive: 28VDC 5A 4A(DB) 25,000cycles
 Resistive: 115VAC, 60Hz 3A 1A(DB) 25,000cycles
 Inductive: 28VDC 2A 2A(DB) 25,000cycles
 Contact Resistance: 50mΩ Max.
 Insulation Resistance: 1GΩ @ 500DVC
 Dielectric Strength: AC 1000V 1 minute
 Mechanical Life: 1,000,000cycles
 Operating Temperature: -40° C ~ +85° C
 Switch action: Momentary
 Switch circuitry: SPDT-DB, load 1N.O./1N.C. 2 Circuit Life
 Actuator Ingress Protection: IP67, IP68S, and IP69K (Front Panel).
 Total travel: 1.6mm max.
 Operating Force : 1.7lbs [770g]. Release Force : 12oz [340g]
 Stands: UL61058 ROHS

Parts List	
1	NUT
2	GASKET



Y	Yellow	黄色
W	White	白色
U	Blue	蓝色
R	Red	红色
G	Green	绿色
B	Black	黑色
CAP COLOR(X)		

广东科斯达电子科技有限公司
 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGLE'S

UNITS MM

DRAWN BY:	DATE	MATL	TITLE	SWITCH
Jack Lu	12/27/22			
CHECKED BY:	DATE	FINISH	MODLE	TACT SWITCH WITH LED
Jacky Chen	12/27/22			
APPROVED BY:	DATE	SCALE	DWG NO.	SIZE
Tony Kao	12/27/22	1 : 1		A4
		SHEET NO.	PART NO.	VER
		1 of 1		R

ITEM NO.	DESCRIPTION	DRAWN	DATE