



### SPECIFICATIONS


Circuit	:SPST
Current rating	:10mA min./100mA max.
Voltage rating	:2V DC min./30V DC max.
Dielectric withstanding voltage	:500VAC for 1 minute
Contact resistance	:50mΩ Max. (Initial)
Insulation resistance	:100MΩ Min.
Operating force	:600±100gf
Total travel	:1.5±0.4mm
Operating life:	:1,000,000 cycles Min
Bounce time:	: ≤ 1ms
Operating speed	100 mm/s(3.94/s)
Solder specifications	:260°C for 5 seconds
Operating temperature	:- 40°C ~ + 85°C
Protection class	: IP40





### MATERIAL:

Base : PA+GF,UL rated:94 V-2 Min;  
 Cap: POM ;  
 Terminal: Brass,Silver plated;

### CIRCUIT



### P.C.B. LAYOUT



 **广东科斯达电子科技有限公司**  
 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.

TOLERANCE UNLESS OTHERWISE STATED:  
 Up to 5 ±0.2  
 Above 5 ~ 15 ±0.3  
 Above 15 ~ 30 ±0.4  
 Above 30 ~ 50 ±0.5  
 Angle ±0.3

3RD. ANGEL'S



UNITS

MM

DRAWN BY:	DATE
Jack Lu	12/27/22
CHECKED BY:	DATE
Jacky Chen	12/27/22
APPROVED BY:	DATE
Tony Kao	12/27/22

MAT'L	TITLE	SWITCH
FINISH	MODLE	TACT SWITCH WITH LED
SCALE	DWG NO.	
SHEET NO.	PART NO.	

SIZE
A4
VER
R

ITEM NO.	DESCRIPTION	DRAWN	DATE