


Specifications


Circuit :SPST
 Current rating :30mA
 Voltage rating :30VDC
 Dielectric withstanding voltage :500VAC for 1 minute
 Contact resistance :100mΩ Max. (Initial)
 Insulation resistance :100MΩ Min
 Operating force :200±50gf
 Total travel :0.7mm±0.2mm
 Operating life :100,000 cycles Min.
 Solder specifications :260±5°C for 5 seconds
 Operating temperature :-20°C ~ +70°C

MATERIAL:
 Frame:PA,UL rated:94 V-2 Min. ;
 Cap:ABS;
 Terminal:Brass,Gold or Tin plated.

CIRCUIT



P.C.B.LAYOUT



A	Gray	灰色
B	Black	黑色
O	Orange	橙色
W	White	白色
U	Blue	蓝色
Y	Yellow	黄色
G	Green	绿色
R	Red	红色
Cap Color (X)		

广东科斯达电子科技有限公司
 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.

TOLERANCE UNLESS OTHERWISE STATED :
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MATL	TITLE	SWITCH
Jack Lu	12/27/22		MODLE	TACT SWITCH WITH LED
CHECKED BY:	DATE	SCALE	DWG NO.	SIZE
Jacky Chen	12/27/22	1 : 1		A4
APPROVED BY:	DATE	SHEET NO.	PART NO.	VER
Tony Kao	12/27/22	1 of 1		R

ITEM NO.	DESCRIPTION	DRAWN	DATE