



SPECIFICATIONS

Circuit :SPST
 Current rating :100mA
 Voltage rating :12VDC
 Dielectric withstanding voltage :250VAC for 1 minute
 (between contacts)
 (between contacts & case)
 Contact resistance :200mΩ Max. (Initial)
 Insulation resistance :100MΩ Min.
 Operating force :250±100gf
 Full travel :4.5mm±0.2mm
 Mechanical life :Over 2,000,000 cycles
 Electrical life :Over 1,000,000 cycles
 Manual welding :350°C for 3 seconds
 Operating temperature :-20°C ~ +70°C
 Function :OFF-(ON)

MATERIAL:

Base:PA+GF,UL rated:94 V-2 Min.
 Cap:PC
 Terminal:Brass, Silver plated;

广东科斯达电子科技有限公司
 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	12/27/22			
CHECKED BY:	DATE	FINISH	MODLE	TACT SWITCH WITH LED
Jacky Chen	12/27/22			
APPROVED BY:	DATE	SCALE	DWG NO.	SIZE
Tony Kao	12/27/22	1 : 1		A4
		SHEET NO.	PART NO.	VER
		1 of 1		R