




**SPECIFICATIONS**

Circuit : SPST  
 Current rating : 10mA min./100mA max.  
 Voltage rating : 2V DC min./30V DC max.  
 Dielectric withstanding voltage : 500VAC for 1 minute  
 Contact resistance : 50mΩ Max. (Initial)  
 Insulation resistance : 100MΩ Min.  
 Operating force : 600±100gf  
 Total travel : 1.5±0.4mm  
 Operating life: : 1,000,000 cycles Min  
 Bounce time: : ≤ 1ms  
 Operating speed 100 mm/s(3.94/s)  
 Solder specifications : 260°C for 5 seconds  
 Operating temperature : - 40°C ~ + 85°C  
 Protection class : IP40



**MATERIAL:**  
 Base : PA+GF,UL rated:94 V-2 Min;  
 Cap: POM ;  
 Terminal: Brass,Silver plated;



**CIRCUIT**



**P.C.B. LAYOUT**



**广东科斯达电子科技有限公司**  
**GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.**

TOLERANCE UNLESS OTHERWISE STATED :  
 Up to 5 ±0.2  
 Above 5 ~ 15 ±0.3  
 Above 15 ~ 30 ±0.4  
 Above 30 ~ 50 ±0.5  
 Angle ±0.3

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	12/27/22			
CHECKED BY:	DATE	FINISH	MODLE	TACT SWITCH WITH LED
Jacky Chen	12/27/22			
APPROVED BY:	DATE	SCALE	DWG NO.	
Tony Kao	12/27/22	1 : 1		
		SHEET NO.	PART NO.	
		1 of 1		

ITEM NO. DESCRIPTION DRAWN DATE