



POLES & CIRCUITS

Plunger Position () = Momentary		Connected Terminals		Throw & Switch/Lamp Schematics	
Normal	Down	Normal	Down	Notes: Switch is marked with NC, NO, COM, L+ & L-. Lamp circuit is isolated and requires an external power source.	
ON ON	(ON) ON	1-3	1-2	SPDT	
ON ON	(ON) ON	1-3 4-6	1-2 4-5	DPDT	

广东科斯达电子科技有限公司
GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	12/27/22			
CHECKED BY:	DATE	FINISH	MODLE	TACT SWITCH WITH LED
Jacky Chen	12/27/22			
APPROVED BY:	DATE	SCALE	DWG NO.	
Tony Kao	12/27/22	1 : 1		
ITEM NO.	DESCRIPTION	DRAWN	DATE	SHEET NO.
				1 of 1
				PART NO.

SIZE
A4
VER
R