



Electrical Characteristics 电气特性

For Fuse	Rated Amperage	Rated Voltage	Operating Power	Contact Resistance	Insulation Resistance	Dielectric Strength
保险丝规格	额定电流	额定电压	额定功率	接触电阻	绝缘电阻	耐压
6 x 30	15A/20A	250V	4W	<5mΩ	>100 MΩ	>1500Vac/60"

- **Material 材料:** Insulating Body 绝缘体: PA66 UL 94 V0  
Lead 导线: 22AWG~14AWG,符合 UL 1015;  
Port 端极: 黄铜电镀
- **Mounting 装配方式:** 插入保险丝对合固定,20A 时须端子与保险丝进行焊接
- **Safety Approvals 安全认证:**


**广东科斯达电子科技有限公司**  
 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2, Above 5 ~ 15 ±0.3, Above 15 ~ 30 ±0.4, Above 30 ~ 50 ±0.5, Angle ±0.3  
 3RD. ANGEL'S  
 UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	12/27/22			
CHECKED BY:	DATE	FINISH	MODLE	TACT SWITCH WITH LED
Jacky Chen	12/27/22			
APPROVED BY:	DATE	SCALE	DWG NO.	SIZE
Tony Kao	12/27/22	1 : 1		A4
		SHEET NO.	PART NO.	VER
		1 of 1		R

ITEM NO.	DESCRIPTION	DRAWN	DATE