RoHS Compliant
2002/95/EC
Process Capable

REV.	ECN. NO.	APPD.















A1	GND	B12	GND
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

NOTES:
1. ELECTRICAL:
   1) CURRENT RATING: 3AMP MAX;
   2) INSULATION RESISTANCE: 100MΩ MIN 250V DC;
   3) CONTACT RESISTANCE: 30mΩ MAX;
   4) WITHSTANDING VOLTAGE: 250V AC;
   5) OPERATING TEMPERATURE:-30°C TO +80°C.
2. Mechanical:
   1) Mating Force: 35N MAX.
   2) Unmating Force: 10N MIN.
3. DIMENSIONS MARKED "▼"
   TO BE CHECKED BY Q.C & IPQC.

4.PART NO.



NO	PARTS	MATERIAL	QTY	FINISHING
5	SHRAPNEL	STAINLESS STEEL	2	
4	HOOK	STAINLESS STEEL	1	
3	SHELL	STAINLESS STEEL	1	PLATED NICKEL
2	TERMINAL	COPPER ALLOY	16	PLATED GOLD
1	HOUSING	LCP+30%GF	1	UL94V-0

.X ±0.30	.X° ±1°
.XX ±0.20	.XX°
.XXX ±0.10	.XXX°

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC
AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC

UNITS mm
MAT'L SEE NOTE
FINISH SEE NOTE
Q'TY

廣東科斯達電子科技有限公司

TITLE: USB TYPE CF 前插后贴16P 板上型 后盖有缺口
PART NO.:
DR: Ricky 2017/12/12
DWG NO.:
CHKD: Ricky 2017/12/12
APPD:

SCALE	SHEET	REV.	CUSTOMER DRAWING
1:1	1/1	B	