



8.	Housing	PBT+15%	1	Black Color
7.	Cover	PA9T	1	Black Color
6.	Make Terminal	0.2T Phosphor Bronze	1	Silver Plated
5.	Shunt Terminal B	0.4T Brass	1	Silver Plated
4.	Shunt Terminal A	0.4T Brass	1	Silver Plated
3.	Ring Spring	0.25T Phosphor Bronze	1	Silver Plated
2.	Tip Spring	0.3T Phosphor Bronze	1	Silver Plated
1.	Earth Terminal	0.5T Bronze	1	Silver Plated
NO.	Description	Material	Q'TY	Finish

广东科斯达电子科技有限公司 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.	DATE	DWN	CHKD	APVD	MANAGER
	12.09.2009				

PART NAME: 3.5 ϕ PHONE JACK	PART NUMBER: SCJ364P00IS0B00G	VERSION: 5.0
----------------------------------	-------------------------------	--------------

TOLERANCE: ± 0.3 mm UNLESS OTHERWISE SPECIFIED	UNIT: mm	SCALE: 1/1
--	----------	------------

SPECIFICATIONS:
 Contact Resistance : 30m Ω max
 Insulation Resistance : 100M Ω min.at DC500V
 Dielectric Withstand Voltage: AC 500V for one minute
 Remark: ? : The Most Important Dimension

RoHS Compliant For Reference
 僅供參考