



| 12 | Spring | SUS-304 | 1 | |
|-----|----------------|-----------------------|------|---------------|
| 11 | Insulator | PA66+33% | 1 | Black Color |
| 10 | Sequins | Tin phosphor bronze | 2 | |
| 9 | Switch Pin | 0.4T Brass | 6 | Silver Plated |
| 8 | Back Housing | PA66+33% | 1 | White Color |
| 7 | Back Housing | PA66+33% | 1 | Black Color |
| 6 | Front Housing | PBT | 1 | Black Color |
| 5 | Tip Spring | 0.25T Phosphor Bronze | 1 | Silver Plated |
| 4 | Break Terminal | 0.4T Brass | 1 | Silver Plated |
| 3 | Break Terminal | 0.4T Brass | 1 | Silver Plated |
| 2 | Ring Spring | 0.3T Phosphor Bronze | 1 | Silver Plated |
| 1 | Earth Terminal | 0.5T Brass | 1 | Silver Plated |
| NO. | Description | Material | Q'TY | Finish |

| | | | | | |
|---|------------|-----|------|------|---------|
| 广东科斯达电子科技有限公司 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD. | DATE | DWN | CHKD | APVD | MANAGER |
| | 09.27.2020 | 王平華 | | | |

| | | |
|---|--------------------------------|-------------|
| PART NAME : 3.5φ PHONE JACK | PART NUMBER : SCJ350P00US0B01G | VERSION:5.0 |
| TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED | UNIT:mm | SCALE:1/1 |

SPECIFICATIONS:
 Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstanding Voltage: AC 500V for one minute
 Remark: ▲: The Most Important Dimension

For Redference
 僅供參攷

RoHS&SVHC
 Compliant