



| 8  | Housing          | PBT+15%G              | 1    | Black Color |
|----|------------------|-----------------------|------|-------------|
| 7  | Shunt Terminal B | 0.2T Phosphor Bronze  | 1    | Gold Plated |
| 6  | Shunt Terminal A | 0.2T Phosphor Bronze  | 1    | Gold Plated |
| 5  | Tip Spring       | 0.25T Brass           | 1    | Gold Plated |
| 4  | Break Terminal B | 0.25T Phosphor Bronze | 1    | Gold Plated |
| 3  | Break Terminal A | 0.2T Phosphor Bronze  | 1    | Gold Plated |
| 2  | Ring Spring      | 0.3T Phosphor Bronze  | 1    | Gold Plated |
| 1  | Earth Terminal   | 0.2T Phosphor Bronze  | 1    | Gold Plated |
| NO | Description      | Material              | Q'TY | Finish      |

|  |   |            |     |      |      |         |
|--|---|------------|-----|------|------|---------|
|  | <b>广东科斯达电子科技有限公司</b><br>GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD. | DATE       | DWN | CHKD | APVD | MANAGER |
|  |   | 01.06.2012 |     |      |      |         |

|                                   |                                |              |
|-----------------------------------|--------------------------------|--------------|
| PART NAME : 3.5 $\phi$ PHONE JACK | PART NUMBER : SCJ376R7GAG0B00G | VERSION: 3.0 |
|-----------------------------------|--------------------------------|--------------|

|   |          |            |
|---|----------|------------|
| TOLERANCE : $\pm 0.3$ mm UNLESS OTHERWISE SPECIFIED | UNIT: mm | SCALE: 1/1 |
|---|----------|------------|

SPECIFICATIONS:  
 Contact Resistance : 30m $\Omega$  max  
 Insulation Resistance : 100M $\Omega$  min. at DC 500V  
 Dielectric Withstanding Voltage: AC 500V for one minute  
 Remark:  $\blacktriangle$ : The Most Important Dimension

RoHS  
Compliant

For Reference  
僅供參考