



Pin Hole Layout
(Jack Bottom View)

6.	Cover	PC	1	Transparent
5.	Housing	POM	1	Black Color
4.	Barrel	Low lead Brass Rod	1	Nickel Plated
3.	Break Terminal	0.3T Brass	1	Silver Plated
2.	Tip Spring	0.2T Phosphor Bronze	1	Silver Plated
1.	Earth Terminal	0.3T Brass	1	Silver Plated
NO.	Description	Material	Q'TY	Finish

	广东科斯达电子科技有限公司 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.	DATE	DWN	CHKD	APVD	MANAGER
		08.24.2020	王平華			

PART NAME : 3.5 ϕ PHONE JACK	PART NUMBER: SCJ328M0NYS0B00L	VERSION: 2.0
-----------------------------------	-------------------------------	--------------

TOLERANCE : $\pm 0.3\text{mm}$ UNLESS OTHERWISE SPECIFIED	UNIT: mm	SCALE: 1/1
---	----------	------------

SPECIFICATIONS:
 Contact Resistance : 30m Ω max
 Insulation Resistance : 100M Ω min. at DC 500V
 Remark: \blacktriangle : The Most Important Dimension

For Reference
 僅供參考
 RoHS&SVHC
 Compliant