



NO.	Description	Material	Q'TY	Finish
6.	Nut	Low Lead Brass Rod	1	Nickel Plated
5.	Housing	PBT	1	Black Color
4.	Tip Spring	0.2T Phosphor Bronze	1	Silver Plated
3.	Break Terminal	0.4T Brass	1	Silver Plated
2.	Ring Spring	0.25T Phosphor Bronze	1	Silver Plated
1.	Earth Terminal	0.25T Phosphor Bronze	1	Silver Plated

<p>广东科斯达电子科技有限公司 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.</p>	DATE	DWN	CHKD	APVD	MANAGER
	07.15.2021	王平華			

PART NAME : 3.5φ PHONE JACK	PART NUMBER: SCJ330P10VS3B00L	VERSION: 2.0
TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED	UNIT: mm	SCALE: 1/1

SPECIFICATIONS:
 Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstanding Voltage: AC 500V for one minute
 Remark: ▲: The Most Important Dimension

For Redference
 僅供參考

RoHS&SVHC
 Compliant