



10	Spring L	SUS-304	1	
9	Spring S	SUS-304	1	
8	Cover	PBT	1	Black Color
7	Housing	PBT	1	Black Color
6	Barrel	Brass	1	Nickel Plated
5	Ring Spring	0.3T Brass	1	Silver Plated
4	Shunt Terminal B	0.3T Brass	1	Silver Plated
3	Tip Spring	0.3T Brass	1	Silver Plated
2	Earth Terminal	0.3T Brass	1	Silver Plated
1	Shunt Terminal A	0.3T Brass	1	Silver Plated
NO	Descripcion	Material	Q'TY	Finish

	广东科斯达电子科技有限公司 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.	DATE	DWN	CHKD	APVD	MANAGER
		01.04.2012				

PART NAME: 3.5φ PHONE JACK	PART NUMBER: SCJ380RONUS0B00G	VERSION: 3.0
TOLERANCE: ±0.3mm UNLESS OTHERWISE SPECIFIED		UNIT: mm
		SCALE: 1/1

Pin Hole Layout
(Jack Bottom View)

RoHS Compliant For Reference
 僅供參考

SPECIFICATIONS:
 Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstanding Voltage: AC 500V for one minute
 Remark: ▲: The Most Important Dimension