



Pin Hole Layout
(Jack Bottom View)

6.	Barrel	Low lead Brass Rod	1	Nickel Plated
5.	Back Cover	PBT	1	Black Color
4.	Housing	PBT	1	Black Color
3.	Ring Spring	0.25T Phosphor Bronze	1	Silver Plated
2.	Tip Spring	0.35T Phosphor Bronze	1	Silver Plated
1.	Earth Spring	0.25T Phosphor Bronze	1	Silver Plated
NO.	Description	Material	QTY	Finish

广东科斯达电子科技有限公司 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.	DATE	DWN	CHKD	APVD	MANAGER
	09.16.2020	王平華			

PART NAME : 3.5 ϕ PHONE JACK PART NUMBER : SCJ340RONASOB00L VERSION:2.0

TOLERANCE : $\pm 0.3\text{mm}$ UNLESS OTHERWISE SPECIFIED UNIT:mm SCALE: /

SPECIFICATIONS:
 Contact Resistance : 30m Ω max
 Insulation Resistance : 100M Ω min. at DC 500V
 Remark: \blacktriangle : The Most Important Dimension

For Redference
僅供參攷

RoHS&SVHC
Compliant