



9.	Nut	2.0T Brass	1	Nickel Plated
8.	Housing	PBT+15%	1	Black Color
7.	Cover	PA9T	1	Black Color
6.	Make Terminal	0.2T Phosphor Bronze	1	Silver Plated
5.	Shunt Terminal B	0.4T Brass	1	Silver Plated
4.	Shunt Terminal A	0.4T Brass	1	Silver Plated
3.	Ring Spring	0.25T Phosphor Bronze	1	Silver Plated
2.	Tip Spring	0.3T Phosphor Bronze	1	Silver Plated
1.	Earth Terminal	0.5T Bronze	1	Silver Plated
NO.	Description	Material	Q'TY	Finish

广东科斯达电子科技有限公司 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.	DATE	DWN	CHKD	APVD	MANAGER
	12.09.2005	易爱娣	陈	李	高

PART NAME: 3.5 ϕ PHONE JACK PART NUMBER: SCJ364P10IS3B00G VERSION: 4.0

TOLERANCE: ± 0.3 mm UNLESS OTHERWISE SPECIFIED UNIT: mm SCALE: 1/1

SPECIFICATIONS:

Contact Resistance: ≤ 30 m Ω max

Insulation Resistance: ≥ 100 M Ω min.at DC500V

Dielectric Withstand Voltage: AC 500V for one minute