



Pin Hole Layout
(Jack Bottom View)

11. Nut	1.5T Brass	1	Nickel Plated
10. Base	Brass	1	Nickel Plated
9. Spring S	SUS-304	1	
8. Spring L	SUS-304	1	
7. Tip Spring	0.25T Brass	1	Silver Plated
6. Slant Terminal	0.3T Brass	1	Silver Plated
5. Slant Terminal	0.3T Brass	1	Silver Plated
4. Ring Spring	0.25T Brass	1	Silver Plated
3. Earth Terminal	0.3T Brass	1	Silver Plated
2. Cover	PBI	1	Black Color
1. Housing	PBT	1	Black Cover
NO. Description	Material	QTY	Finish

广东科斯达电子科技有限公司
GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.

DATE	DWN	CHKD	APVD	MANAGER
07.27.2017	丁平	陈平	陈平	陈平

REFN
Conflict

PART NAME: 3.5Φ PHONE JACK	PART NUMBER: SOL158R4NUS1H00G	VERSION: 5.0
TOLERANCE: ±0.3mm UNLESS OTHERWISE SPECIFIED	UNIT: mm	SCALE: 1/1

SYMBOLICATIONS:
 Contact Resistance: 100-0 max
 Insulation Resistance: 20MΩ min. at DC 500V
 Dielectric Withstanding Voltage: AC 250V for one minute
 Symbol: ▲ The Mark Impression Dimension