



Pin Hole Layout
(Jack Bottom View)

7.	Insulator	PBT	1	Black Color
6.	Housing	PA66+33%GF	1	Black Color
5.	Sping CN Terminal	0.20T Phosphor Copper	1	Silver Plated
4.	Sping CO Terminal	0.20T Phosphor Copper	1	Silver Plated
3.	Sping 4 Terminal	0.25T Phosphor Copper	1	Silver Plated
2.	Sping 3 Terminal	0.20T Phosphor Copper	1	Silver Plated
1.	Sping 1 Terminal	0.5T Bronze	1	Silver Plated
NO.	Description	Material	Q'TY	Finish

DATE	DWN	CHKD	APVD	MANAGER
09.14.2020	王平華			

广东科斯达电子科技有限公司
GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.

PART NAME : 3.5φ PHONE JACK PART NUMBER: SCJ300P00RS0B00G VERSION: 4.0

TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED UNIT: mm SCALE: 1/1

SPECIFICATIONS:
Contact Resistance : 30mΩ max
Insulation Resistance : 100MΩ min. at DC 500V
Remark: ▲ The Most Important Dimension

For Reference
僅供參攷

RoHS&SVHC
Pb Free Process