



6	NUT(1.5T )	Low lead Brass Rod	1	Nickel Plated
5	Housing	POM	1	Black Color
4	Barrel	Low lead Brass Rod	1	Nickel Plated
3	Ring Spring	0.2T Phosphor Bronze	1	Silver Plated
2	Tip Spring	0.2T Phosphor Bronze	1	Silver Plated
1	Earth Terminal	0.3T Brass	1	Silver Plated
NO.	Description	Material	Q'TY	Finish

	<b>广东科斯达电子科技有限公司</b> GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.	DATE	DWN	CHKD	APVD	MANAGER
		08.20.2020	王平華			

PART NAME : 3.5 $\phi$ PHONE JACK	PART NUMBER: SCJ311M1NXS1B00L	VERSION: 1.0
-----------------------------------	-------------------------------	--------------

TOLERANCE : $\pm 0.3$ mm UNLESS OTHERWISE SPECIFIED	UNIT: mm	SCALE: 1/1
---	----------	------------

SPECIFICATIONS:  
 Contact Resistance : 30m $\Omega$  max  
 Insulation Resistance : 100M $\Omega$  min. at DC 500V  
 Remark: ▲ : The Most Important Dimension

For Redference  
 僅供參攷

RoHS&SVHC  
 Compliant