



NUT

11	Nut	Brass	1	Nickel Plated
10	Spring L	SUS-304	1	
9	Spring S	SUS-304	1	
8	Cover	PBT	1	Black Color
7	Housing	PBT	1	Black Color
6	Barrel	Brass	1	Nickel Plated
5	Ring Spring	0.3T Brass	1	Silver Plated
4	Shunt Terminal B	0.3T Brass	1	Silver Plated
3	Tip Spring	0.3T Brass	1	Silver Plated
2	Earth Terminal	0.3T Brass	1	Silver Plated
1	Shunt Terminal A	0.3T Brass	1	Silver Plated
NO	Descripcion	Material	Q'TY	Finish

SPECIFICATIONS:

Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstand Voltage : AC 500V for one minute
 Remark: ▲ : The Most Important Dimension

RoHS
Compliant

	广东科斯达电子科技有限公司 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.	DATE	DWN	CHKD	APVD	MANAGER
		03.11.2009	阮雲軍			

PART NAME: 3.5φ PHONE JACK	PART NUMBER: SCJ380M6NUS3B00G	VERSION:1.0
----------------------------	-------------------------------	-------------

TOLERANCE :±0.3mm UNLESS OTHERWISE SPECIFIED	UNIT:mm		SCALE:1/1
--	---------	--	-----------