




WASHER



DETAIL A

NUT

10/16T NPTXG THREAD



Pin Hole Layout
(Jack Bottom View)

7. Washer	0.5" Steel	1	Nickel Plated
8. Nut	2.0" Steel	1	Nickel Plated
5. Cover	PA6	1	Black Color
4. Holding	PE	1	Black Color
3. Bushing	Brass	1	Nickel Plated
2. Tip Spring	0.4" Phosphor Bronze	1	Silver Plated
1. Earth Terminal	0.2" Phosphor Bronze	1	Silver Plated
NO	Description	Material	Qty Finish

广东科斯达电子科技有限公司
GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.

DATE	DWN	CHKD	APVD	MANAGER
25.10.2017	王个平	陈永强	陈永强	陈永强

PART NAME : 6.3e PHONE JACK	PART NUMBER : SOJ63DRONAS-BH0G	VERSION: 6.0
TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED	UNIT: mm	SCALE: 1/1

SPECIFICATIONS:
 Contact Resistance : 30mΩ max.
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstanding Voltage: AC 500V for one minute
 Remark: ▲: The Most Important Dimension

ROSS
0.2mm ACT